

SAFETY DATA SHEET



Lysol® Brand III Disinfectant Spray, All Scents (Aerosol)

1. Product and company identification

Product name	:	Lysol® Brand III Disinfectant Spray, All Scents (Aerosol)
Supplier	:	Reckitt Benckiser (Canada) Inc. 1680 Tech Avenue, Unit #2 Mississauga, Ontario L4W 5S9 CANADA Telephone: +1 905 283 7000
SDS #	:	D0224478
Formulation #:	:	1178-172 (0175917) Crisp Linen 1338-015 (0175918) Spring Waterfall 1338-018 (0175934) Green Apple / Green Apple Breeze 1338-021 (0175938) Crisp Berry 1338-019 (0175919) Country
DIN #	:	02279177
UPC Code / Sizes	:	Size: 350 gm. & 164 gm. & 28 gm. (Tin plate steel cans). Crisp Linen, 59631-34052 (350 gm.); 59631-82492 (164 gm.); 59631-79939 (28 gm.) Spring Waterfall, 59631-75571 (350 gm.) Green Apple / Green Apple Breeze, 59631-77786 (350 gm.) Crisp Berry, 59631-78002 (350 gm.) Country, 59631-34082 (350 gm.)
Manufacturer	:	Reckitt Benckiser LLC. Morris Corporate Center IV 399 Interpace Parkway (P.O. Box 225) Parsippany, New Jersey 07054-0225 +1 973 404 2600
Validation date	:	16/05/2012.
Emergency telephone number	:	1-800-338-6167
Transport Emergency phone:	:	1-800-424-9300 (U.S. & Canada) CHEMTREC Outside U.S. and Canada (North America), call Chemtrec:703-527-3887

2. Hazards identification

Emergency overview

Physical state	:	Liquid.
Color	:	Clear.
Odor	:	Characteristic.
Signal word:	:	DANGER
Hazard statements	:	EXTREMELY FLAMMABLE. CONTAINER MAY EXPLODE IF HEATED
Precautionary measures	:	Keep out of reach of children. Do not puncture, incinerate or store the container at temperatures above 120°F or in direct sunlight. Use only with adequate ventilation. Do not breathe gas/fumes/vapor/spray. Do not get on skin or clothing. Avoid contact with eyes. and Food Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
OSHA/HCS status	:	This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential acute health effects

Skin	:	Slightly irritating to the skin.
-------------	---	----------------------------------

D0224478

2. Hazards identification

- Eyes** : Moderately irritating to eyes.
- Potential chronic health effects**
- Chronic effects** : Contains material that may cause target organ damage, based on animal data.
- Carcinogenicity** : Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
- Target organs** : Contains material which may cause damage to the following organs: the nervous system, liver, heart, upper respiratory tract, central nervous system (CNS).
- Over-exposure signs/symptoms**
- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.
- Hazard statements** :



Extremely flammable

3. Composition/information on ingredients

Name	CAS number	%
Ethanol	64-17-5	30 - 60
n-butane	106-97-8	2.5 - 5
Propane	74-98-6	1 - 2.5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

- First aid**
- Eye contact** : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.
- Skin contact** : Get medical attention immediately. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse.
- Inhalation** : Move exposed person to fresh air. Get medical attention immediately.
- Ingestion** : Call medical doctor or poison control center immediately. Wash out mouth with water.
- Protection of first-aiders** : Use personal protective equipment as required.
- Notes to physician** : Contains denatured ethanol; ingestion may result in ethanol poisoning.

D0224478

5. Fire-fighting measures

Extinguishing media

Suitable Use an extinguishing agent suitable for the surrounding fire.

Not suitable None known.

Special hazards arising from the substance or mixture

Special exposure hazards Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Hazardous thermal decomposition products Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

NFPA (30B) aerosol Flammability Level 1

Fire or projection hazard. Aerosol cans may explode with extreme heat and become projectiles.

Advice for firefighters

Special protective equipment for fire-fighters Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Special remarks on explosion hazards

Sensitivity to mechanical impact Not available.

Sensitivity to static discharge Not available.

6. Accidental release measures

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

D0224478

7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Avoid exposure - obtain special instructions before use. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Empty containers retain product residue and can be hazardous.

Do not puncture or incinerate CONTENTS UNDER PRESSURE

Storage

: Do not store above the following temperature: 50°C (120°F). Store in accordance with local regulations. Store in a segregated and approved area. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

CONTAINERS SHOULD BE KEPT OUT OF REACH OF CHILDREN. Pressurised container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn after use. Keep away from all sources of ignition. Fires involving flammable aerosols are severe and can spread very quickly. Warehouses and stores containing aerosols should therefore be separated from other areas by a fire resistant construction of at least one half hour duration. Stores should be well ventilated, particularly at low levels. The natural ventilation in a large open warehouse building will normally be suitable. Avoid the storage of aerosols in basements where practicable.

EPA Product

: It is a violation of federal law to use this product in a manner inconsistent with its labeling.

8. Exposure controls/personal protection

Occupational exposure limits		TWA (8 hours)			STEL (15 mins)			Ceiling (ACGIH TLV)			
Ingredient	List name	ppm	mg/m³	Other	ppm	mg/m³	Other	ppm	mg/m³	Other	Notations
Butane	US ACGIH 2/2010	1000	-	-	-	-	-	-	-	-	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 9/2010	600	-	-	750	-	-	-	-	-	
	ON 7/2010	800	-	-	-	-	-	-	-	-	
	QC 6/2008	800	1900	-	-	-	-	-	-	-	
Ethanol	US ACGIH 2/2010	-	-	-	1000	-	-	-	-	-	
	AB 4/2009	1000	1880	-	-	-	-	-	-	-	
	BC 9/2010	-	-	-	1000	-	-	-	-	-	
	ON 7/2010	-	-	-	1000	-	-	-	-	-	
	QC 6/2008	1000	1880	-	-	-	-	-	-	-	
Propane	US ACGIH 2/2010	1000	-	-	-	-	-	-	-	-	
	AB 4/2009	1000	-	-	-	-	-	-	-	-	
	BC 9/2010	1000	-	-	-	-	-	-	-	-	
	ON 7/2010	1000	-	-	-	-	-	-	-	-	
	QC 6/2008	1000	1800	-	-	-	-	-	-	-	

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Manufacturer: Exposure controls

Engineering measures

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

D0224478

8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

- Physical state** : Liquid.
- Flash point** : Closed cup: 25.6°C (78.1°F)
- Burning time** : Not applicable.
- Burning rate** : Not applicable.
- Auto-ignition temperature** : Not available.
- Flammable limits** : Not available.
- Color** : Clear.
- Odor** : Characteristic.
- Taste** : Not available.
- Molecular weight** : Not applicable.
- Molecular formula** : Not applicable.
- pH** : 10.8 to 11.8
- Boiling/condensation point** : Not available.
- Melting/freezing point** : Not available.
- Critical temperature** : Not available.
- Relative density (g/ml)** : Not available.
- Bulk density** : 7.1 to 7.5 lbs/gal
- Vapor pressure** : Not available.
- Vapor density** : Not available.
- Volatility** : Not available.
- Odor threshold** : Not available.
- Evaporation rate** : Not available.
- SADT** : Not available.
- Viscosity** : Not available.

D0224478

9. Physical and chemical properties

- Ionicity (in water)** : Not available.
- Dispersibility properties** : Not available.
- Solubility** : Easily soluble in the following materials: cold water and hot water.
- Physical/chemical properties comments** : Not available.
- Aerosol product**
- Type of aerosol** : Spray

10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Conditions to avoid** : Keep away from extreme heat. Protect from moisture. Keep from freezing.
Do not store above 50°C
- Incompatible materials** : Do not mix with Other Products
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Butane	LC50 Inhalation Vapor	Rat	658000 mg/m3	4 hours
Ethanol	LC50 Inhalation Vapor	Rat	124700 mg/m3	4 hours
	LD50 Oral	Rat	7 g/kg	-

Conclusion/Summary : Not available.

Chronic toxicity

Product/ingredient name	Result	Species	Dose
Not available.			

Conclusion/Summary : Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.06666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	400 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 milligrams	-

- Skin** : Slightly irritating to the skin.
- Eyes** : Moderately irritating to eyes.

D0224478

11. Toxicological information

Respiratory : Not available.

Sensitizer

Product/ingredient name	Route of exposure	Species	Result
Not available.			

Skin : Not available.

Respiratory : Not available.

Carcinogenicity

Product/ingredient name	Result	Species	Dose
Not available.			

Conclusion/Summary : Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
Ethanol	A3	1	-	-	-	-

Mutagenicity

Product/ingredient name	Test	Experiment	Result
Not available.			

Conclusion/Summary : Not available.

Teratogenicity

Product/ingredient name	Result	Species	Dose
Not available.			

Conclusion/Summary : Not available.

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose
Not available.					

Conclusion/Summary : Not available.

Synergistic products : Not available.

12. Ecological information

Ecotoxicity : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
Ethanol	Acute EC50 17.921 mg/L Marine water Acute EC50 2000 ug/L Fresh water Acute LC50 25500 ug/L Marine water Acute LC50 42000 ug/L Fresh water Chronic NOEC 0.375 ul/L Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franchiscana - Larvae Fish - Oncorhynchus mykiss Fish - Gambusia holbrooki - Larvae - 3 days	96 hours 48 hours 48 hours 4 days 12 weeks

Conclusion/Summary : Not available.

Persistence/degradability

D0224478

12. Ecological information

Product/ingredient name	Test	Result	Dose	Inoculum
Not available.				






- Conclusion/Summary** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Bioconcentration factor** : Not available.
- Mobility** : Not available.
- Toxicity of the products of biodegradation** : Not available.
- Other adverse effects** : No known significant effects or critical hazards.

13. Disposal considerations

- Waste disposal** : Waste must be disposed of in accordance with federal, state and local environmental control regulations. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
TDG Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
Mexico Classification	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IMDG Class	UN1950	Aerosols, flammable	2.1	-		Limited quantity
IATA-DGR Class	UN1950	Aerosols, flammable	2.1	-		See DG List

PG* : Packing group

D0224478

15. Regulatory information

United States

- U.S. Federal regulations** : TSCA 8(a) PAIR: tert-Butyl alcohol
SARA 302/304/311/312 extremely hazardous substances: No products were found.
SARA 302/304 emergency planning and notification: No products were found.
SARA 302/304/311/312 hazardous chemicals: Ethanol; Propane; Butane
SARA 311/312 MSDS distribution - chemical inventory - hazard identification:
 Ethanol: Fire hazard, Immediate (acute) health hazard, Delayed (chronic) health hazard;
 Propane: Fire hazard, Sudden release of pressure; Butane: Fire hazard, Sudden release of pressure
Clean Water Act (CWA) 311: ammonia, anhydrous
Clean Air Act (CAA) 112 regulated flammable substances: Butane; Propane
- Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs)** : Not listed
- Clean Air Act Section 602 Class I Substances** : Not listed
- Clean Air Act Section 602 Class II Substances** : Not listed
- DEA List I Chemicals (Precursor Chemicals)** : Not listed
- DEA List II Chemicals (Essential Chemicals)** : Not listed

State regulations

- Massachusetts** : The following components are listed: ETHYL ALCOHOL; BUTANE; PROPANE
- New York** : None of the components are listed.
- New Jersey** : The following components are listed: ETHYL ALCOHOL; ALCOHOL; BUTANE; PROPANE
- Pennsylvania** : The following components are listed: DENATURED ALCOHOL; BUTANE; PROPANE
- California Prop. 65**

Not available.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
No listed substance				

Canada

- WHMIS (Canada)** : Class B-2: Flammable liquid
 Class B-5: Flammable aerosol.
 Class D-2B: Material causing other toxic effects (Toxic).

Canadian lists

- Canadian NPRI** : The following components are listed: Ethyl alcohol; Butane; Propane
- CEPA Toxic substances** : None of the components are listed.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

D0224478

16. Other information

Hazardous Material Information System (U.S.A.) :

Health	*	1
Flammability		3
Physical hazards		0
Personal protection		B

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.) :



NFPA (30B) aerosol Flammability Level 1

Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of issue : 16/05/2012.
Date of previous issue : No previous validation.
Version : 1
Prepared by :
 Reckitt Benckiser LLC.
 Product Safety Department
 1 Philips Parkway
 Montvale, New Jersey 07646-1810 USA.
 FAX: 201-476-7770

☑ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.