

HASA 12.5% SODIUM HYPOCHLORITE SOLUTION

Safety Data Sheet

12.5% Sodium Hypochlorite

Emergency 24 Hour Telephone: CHEMTREC 800.424.9300

Corporate Headquarters: Hasa Inc.

P.O. Box 802736

Santa Clarita, CA 91355 Telephone • 661.259.5848 Fax • 661.259.1538

		SECTION 1:	IDENTIFICATION
1.1	Produ	uct Identification:	
	1.1.1	Product Name:	HASA 12.5% SODIUM HYPOCHLORITE SOLUTION
	1.1.2	CAS # (Chemical Abstracts Service):	7681-52-9
	1.1.3	RTECS (Registry of Toxic Effects of Chemical Substances):	NH3486300
	1.1.4	EINECS (European Inventory of Existing Commercial Substances):	231-668-3
	1.1.5	EC Number:	231-668-3
	1.1.6	Synonym:	Bleach, Hypo, Hypochlorite, Liquid Chlorine Solution
	1.1.7	Chemical Name:	Sodium Hypochlorite
	1.1.8	Chemical Formula:	NaOCI
1.2	Reco	mmended Uses:	Manufacturing Use Only Product (MUP). Industrial repackaging. Chemical intermediate or formulation.
1.3	Comp	pany Identification:	Hasa Inc. P. O. Box 802736 Santa Clarita, CA 91355
1.4	Emergency Telephone Number:		CHEMTREC
			1-800-424-9300
			(24 hour Emergency Telephone)
1.5	Non-E	Emergency Assistance:	661-259-5848
			(8 AM – 5 PM PST / PDT)

Revision Date: 07/01/2015 (Supersedes previous revisions)

SECTION 2: HAZARD(S) IDENTIFICATION				
HEALTH HAZARD	Skin corrosion / irritation:	Category 1		
	Serious Eye damage / Eye Irritation	Category 1		
	Specific target organ toxicity, single exposure	Category 3 (respiratory tract irritation)		
ENVIRONMENTAL HAZARD	Hazardous to the aquatic environment, acute hazard	Category 1		
PHYSICAL HAZARD	Corrosive to metals.	Category 1		
SYMBOLS		! ₹ 2		
SIGNAL WORD	D	ANGER		
HAZARD STATEMENT	May be corrosive to metals. Causes severe skin burns and eye damage. May cause respiratory irritation. Very toxic to aquatic life.			
PRECAUTIONARY	Prevention			
STATEMENT	Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe mist or vapor. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Keep only in original container. Avoid release to the environment.			
	Response			
	If swallowed: Rinse mouth. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage. Collect spillage. Storage and Disposal			
	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container. Dispose of container/contents in accordance with local, regional, national, international regulations as specified.			

	SECTION 3: COMPOSITION INFORMATION ON INGREDIENTS					
	Ingredient	Synonyms	CAS No.	Weight %		
3.1	Sodium Hypochlorite	Bleach	7681-52-9	12.5%		
3.2	Sodium Hydroxide	Caustic Soda	1310-73-2	0.2%		

		SECTION 4: FIRST AID MEASURES
4.1	IF IN EYES	 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
4.2	IF ON SKIN OR CLOTHING	 Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
4.3	IF INHALED	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.
4.4	IF SWALLOWED	 Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
		HOT LINE NUMBER
go		ntainer or label with you when calling a poison control center or doctor, or You may also contact 1-800-424-9300 for emergency medical treatment

		SECTION 5: FIF	RE FIGHTING MEASURES
5.1	Flash	Point:	Not applicable.
5.2		mability:	Nonflammable and noncombustible.
5.3	Auto-	Ignition Temperature:	Not applicable.
5.4	Produ	ucts of Combustion:	Not pertinent.
5.5	Fire F	łazards:	May decompose, generating irritating chlorine gas.
5.6	Explo	sion Hazards:	Not explosive.
5.7	Fire Fighting Media and Instructions:		
	5.7.1	Extinguishing Media:	Water fog. Foam. Dry chemical powder. Carbon dioxide.
	5.7.2	Small Fires:	Use carbon dioxide, or water spray.
	5.7.3	Large Fires:	Use flooding quantities of water as fog.
5.8	Speci	al Remarks on Fire Hazards:	Do not use Mono Ammonium Phosphate (MAP) fire extinguishers. Such use may cause explosion with release of toxic gases.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage.

	SEC	CTION 6: ACCIDENTAL RELEASE MEASURES
6.1	Small Spill:	Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.2	Large Spill:	Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Never return spills in original containers for re-use. For waste disposal, see Section 13 of the SDS.
6.3	Personal Precautions, Protective Equipment & Emergency Procedures:	Keep unnecessary personnel away. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Absorb spillage to prevent material damage. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see Section 8 of the SDS.
6.4	Environmental Precautions:	Do not discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

		SECTION 7: HANDLING AND STORAGE
7.1	Handling:	 Avoid contact with skin or eyes. Do not ingest. Avoid inhalation of vapor or mist. Wear protective equipment if necessary. Mix only with water in accordance with label directions. Mixing this product with ammonia, acids, detergents, etc or with organic materials, e.g. feces, urine, etc. will release chlorine gas, which is irritating to eyes, lungs, and mucous membranes.
7.2	Hygiene Measures:	 Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. While handling this product, avoid eating, drinking or smoking.
7.3	Storage:	 Do not freeze. Store in a cool, shaded outdoor area. Inside storage should be in a cool, dry, well-ventilated area. To maintain hypochlorite strength, do not store in direct or heated indoor areas. Keep in original vented container.
		 Keep in original vented container. Keep container closed when not in use. Do not store adjacent to chemicals that may react if spillage occurs. If closed containers become heated, vent to release decomposition products (mainly oxygen under normal decomposition).

STEL (Short Term Exposure Limit) of 1 p chlorine. 8.2.1 Eye / Face Protection: 8.2.2 Skin Protection: Skin Protection: Wear safety glasses, goggles or face shi prevent eye contact. Wear appropriate chemical resistant prot clothing and chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or I Gloves should be worn when handling th material. Wear chemical resistant clothing a rubber apron when splashing may occumediately if skin is contaminated. Rem contaminated clothing promptly and wash reuse. Clean protective equipment before Avoid breathing vapor or mist. When airb exposure limits are exceeded (see below NIOSH approved respiratory protection exporpropriate to the material and/or its come Full facepiece equipment is recommende used, replaces need for face shield and coggles. For emergency and other condition where exposure limit may be significantly exceeded, use an approved full face posis pressure, self-contained breathing apparative exposure limit may be significantly exceeded, use an approved full face posis pressure, self-contained breathing apparative exceeded in the province of the province	No.		CTION 8: EXPOSURE CON			
8.2.1 Eye / Face Protection: 8.2.2 Skin Protection: 8.2.2 Skin Protection: 8.2.3 Respiratory Protection: 8.2.4 Other Safety Equipment: 8.2.4 Other Safety Equipment: 8.2.5 AlHA (American Industrial Hygiene Association) / WEEL (Workplace Environmental Exposure Level guides) 2010 8.2.4 ACGIH (American Conference of Governmental Industrial Hygienies) TWA (Time Weighted Average) 8.3.5 ACGIH Celling 8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Limite) 8.3.7 OSHA STEL (Short Term Exposure Limite) 8.3.7 OSHA STEL (Short Term Exposure Limite) Wear safety glasses, goggles or face shie prevent eye contact. Wear appropriate chemical resistant prot clothing and chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or Gloves should be worn when handling in material. Wear chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or Gloves should be worn when handling in material. Wear chemical resistant prot clothing and chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or Gloves should be worn when handling in material. Wear chemical resistant prot clothing appare and chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or Gloves should be worn when handling in a rubber appared was reuse. Clean protective equipment is recommended used, replaced respiratory protection e appropriate to the material. Wear chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or Gloves should be worn when handling in material. Wear chemical resistant gloves to skin contact. Butyl rubber, Neoprene and thematerial. Wear chemical resistant gloves to skin contact. Butyl rubber, Neoprene and thematerial. Wear chemical resistant gloves to skin contact. Butyl rubber on the material. Wear chemical resistant protect inmediate Jarking may cere. 8.2.4 Other Safety Equipment: 8.2.5 ACGIH Camerican Industrial Hygiene Acgin Hypochlorite 8.3.6 ACGIH Ceiling 8.3.7 OSHA PEL (Permisi	8.1	Engi	neering Controls:	STEL (Short Term Exposur		
prevent eye contact. Wear appropriate chemical resistant prot olthing and chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or I Gloves should be worn when handling th material. Wear chemical resistant clothing a rubber apron when splashing may occu immediately if skin is contaminated. Rem contaminated clothing promptly and was reuse. Clean protective equipment before Avoid breathing vapor or mist. When airb exposure limits are exceeded (see below NIOSH approved respiratory protection e appropriate to the material and/or its com Full facepiece equipment is recommende used, replaces need for face shield and goggles. For emergency and other condit where exposure limit may be significantly exceeded, use an approved full face posi pressure, self-contained breathing appara Eye wash facility and emergency shower be in close proximity. 8.2.4 Other Safety Equipment: 8.3.1 AIHA (American Industrial Hygiene Association) / WEEL (Workplace Environmental Exposure Level guides) 2010 8.3.2 ACGIH (American Conference of Governmental Industrial Hygienists) TWA (Time Weighted Average) 8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling Not established.	8.2	Perso	onal Protection:			
8.2.2 Skin Protection: Wear appropriate chemical resistant prot clothing and chemical resistant gloves to skin contact. Butyl rubber, Neoprene, or I Gloves should be worn when handling the material. Wear chemical resistant clothing a rubber apron when splashing may occummediately if skin is contaminated. Rem contaminated clothing promptly and wast reuse. Clean protective equipment before Avoid breathing vapor or mist. When airb exposure limits are exceeded (see below NIOSH approved respiratory protection e appropriate to the material and/or its com Full facepiece equipment is recommende used, replaces need for face shield and c goggles. For emergency and other condit where exposure limit may be significantly exceeded, use an approved full face posi pressure, self-contained breathing appare Eye wash facility and emergency shower be in close proximity. 8.3 Exposure Limits: Sodium Hypochlorite 8.3.1 AIHA (American Industrial Hygiene Association) / WEEL (Workplace Environmental Exposure Level guides) 2010 8.3.2 ACGIH (American Conference of Governmental Industrial Hygienists) TWA (Time Weighted Average) 8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling Not established.		8.2.1	Eye / Face Protection:	Wear safety glasses, goggles or face shield to prevent eve contact.		
8.2.3 Respiratory Protection: Avoid breathing vapor or mist. When airb exposure limits are exceeded (see below NIOSH approved respiratory protection e appropriate to the material and/or its come rull facepiece equipment is recommende used, replaces need for face shield and or goggles. For emergency and other condit where exposure limit may be significantly exceeded, use an approved full face posi pressure, self-contained breathing apparate services and self-contained breathing apparate services are in close proximity. 8.3.1 AIHA (American Industrial Hygiene Association) / WEEL (Workplace Environmental Exposure Level guides) 2010 8.3.2 ACGIH (American Conference of Governmental Industrial Hygienists) TWA (Time Weighted Average) 8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling Not established.		8.2.2	Skin Protection:	Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Butyl rubber, Neoprene, or Nitrile Gloves should be worn when handling this material. Wear chemical resistant clothing such as a rubber apron when splashing may occur. Rinse immediately if skin is contaminated. Remove contaminated clothing promptly and wash before reuse. Clean protective equipment before rouse.		
be in close proximity. 8.3 Exposure Limits: 8.3.1 AIHA (American Industrial Hygiene Association) / WEEL (Workplace Environmental Exposure Level guides) 2010 8.3.2 ACGIH (American Conference of Governmental Industrial Hygienists) TWA (Time Weighted Average) 8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling 8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Not established. 8.3.8 Not established. 8.3.9 Not established. 8.30 Not established. 8.31 Not established. 8.32 Not established. 8.33 Not established. 8.34 Not established. 8.35 Not established. 8.36 Not established. 8.37 OSHA STEL (Short Term Exposure Not established.		8.2.3	Respiratory Protection:	Avoid breathing vapor or mexposure limits are exceeded NIOSH approved respirator appropriate to the material Full facepiece equipment is used, replaces need for face goggles. For emergency and where exposure limit may be exceeded, use an approved	ist. When airborne ed (see below), use by protection equipment and/or its components. recommended and, if e shield and chemical do ther conditions is significantly diffull face positive-	
8.3.1 AIHA (American Industrial Hygiene Association) / WEEL (Workplace Environmental Exposure Level guides) 2010 8.3.2 ACGIH (American Conference of Governmental Industrial Hygienists) TWA (Time Weighted Average) 8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling 8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Not established. 8.3.8 NIOSH (Short Term Exposure Not established. 8.3.9 OSHA STEL (Short Term Exposure Not established. 8.3.10 Not established. 8.3.11 Not established. 8.3.12 Not established. 8.3.13 Not established. 8.3.14 Not established. 8.3.15 Not established. 8.3.16 Not established. 8.3.17 Not established. 8.3.17 Not established. 8.3.17 Not established. 8.3.18 Not established. 8.3.19 Not established. 8.3.19 Not established. 8.3.19 Not established. 8.3.10 Not established. 8.3.17 Not established. 8.3.18 Not established. 8.3.19 Not established. 8.3.19 Not established. 8.3.19 Not established. 8.3.19 Not established.		8.2.4	Other Safety Equipment:	Eye wash facility and emerg		
Association) / WEEL (Workplace Environmental Exposure Level guides) 2010 8.3.2 ACGIH (American Conference of Governmental Industrial Hygienists) TWA (Time Weighted Average) 8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling Not established.	3.3	Exposure Limits:		Sodium Hypochlorite	Chlorine*	
8.3.2 ACGIH (American Conference of Governmental Industrial Hygienists) TWA (Time Weighted Average) 8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling 8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Not established. Not established. Not established. Not established. 1 ppm as C		8.3.1	Association) / WEEL (Workplace Environmental Exposure Level	(Short-term time weighted	Not established	
8.3.3 ACGIH STEL (Short Term Exposure Limit) 8.3.4 OSHA PEL (Permisible Exposure Limit) 8.3.5 ACGIH Ceiling 8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Not established. 1 ppm 0.5 ppm Not established. 1 ppm 1 ppm 1 ppm Not established. 1 ppm as C	Material de activité est décide de la constitución	8.3.2	Governmental Industrial Hygienists)	Not established.	0.5 ppm	
Limit) 8.3.5 ACGIH Ceiling Not established. Not establis 8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Not established. 1 ppm as C		8.3.3	ACGIH STEL (Short Term Exposure	Not established.	1 ppm	
8.3.5 ACGIH Ceiling Not established. Not established. 8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Not established. 1 ppm as C		8.3.4	OSHA PEL (Permisible Exposure	Not established.	0.5 ppm	
8.3.6 NIOSH (National Institute for Occupational Safety & Health) IDLH (Immediate Danger to Life & Health) 8.3.7 OSHA STEL (Short Term Exposure Not established. 1 ppm as C		8.3.5	ACGIH Ceiling	Not established.	Not established	
	obnosper e reto oprode anamojo dabjero		NIOSH (National Institute for Occupational Safety & Health) IDLH			
	The state of the s	8.3.7		Not established.	1 ppm as Cl ₂	
8.3.8 NIOSH (15 min. ceiling) Not established. 0.5 ppm * Chlorine is unlikely to be present as a decomposition product, but may be present in					0.5 ppm	

	SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
9.1	Appearance:	Greenish yellow liquid.	
9.2	Odor:	Pungent.	
9.3	Odor Threshold:	0.9 mg/m ³ .	
9.4	pH:	11.2 – 11.4 (1% solution)	
9.5	Melting Point:	Not pertinent.	
9.6	Freezing point:	-23.3°C (-10°F)	
9.7	Boiling Point & Boiling Range:	Decomposes @ 110 °C (230 °F)	
9.8	Flash Point:	No information available.	
9.9	Evaporation Rate:	No information available.	
9.10	Flammability (solid, gas):	Not flammable.	
9.11	Upper / Lower Flammability or Explosive Limits:	No information available.	
9.12	Vapor Pressure:	12.1 mm Hg @ 20 °C (68 °F)	
9.13	Vapor Density:	2.61 (air=1)	
9.14	Relative Density (Specific Gravity):	1.2 g/mL or 10 lb/gallon @ 20 °C (68 °F)	
9.15	Solubility in Water:	Mixes infinitely with water.	
9.16	Partition Coefficient: (n-octanol / water):	No information available.	
9.17	Auto-ignition Temperature:	No information available.	
9.18	Decomposition Temperature:	Decomposes @ 110 °C (230 °F)	
9.19	Molecular Weight:	74.5 g/mole	
9.20	Viscosity:	1.75 - 2.50 centipoises (varies with temperature)	

	SECTION 10: STABILITY AND REACTIVITY		
10.1	Stability:	Stable under normal conditions of storage, handling, and use.	
10.2	Instability / Decomposition Temperature:	All bleach decomposition is dependent on temperature. For any given temperature, the higher the strength, the faster it decomposes. In summary, for every 10°C increase in storage temperature, the sodium hypochlorite will decompose at an increased rate factor of approximately 3.5.	
10.3	Conditions of Instability:	High heat, ultraviolet light.	
10.4	Incompatibility with Various Substances:	Oxidizing agents, acids, nitrogen containing organics, metals, iron, copper, nickel, cobalt, organic materials, and ammonia.	
10.5	Corrosivity:	Corrosive to metals.	
10.6	Special Remarks on Reactivity:	Rate of decomposition increases with heat. May develop chlorine if mixed with acidic solutions.	
10.7	Special Remarks on Corrosivity:	None.	
10.8	Hazardous Polymerization:	Will not occur.	

	SECTION 11: TOXICOLOGICAL INFORMATION		
11.1	Routes of Entry:	Eyes, skin, ingestion, dermal absorption.	
11.2	Acute Toxicity:		
	11.2.1 Oral Toxicity (LD ₅₀):	3-5 g/kg (rat)	
	11.2.2 Dermal Toxicity (LD ₅₀):	>2 g/kg (rabbit)	
	11.2.3 Primary Eye Irritation:	Corrosive	
	11.2.4 Primary Skin Irritation:	Corrosive	
	11.2.5 Inhalation Toxicity (LC ₅₀):	No data available.	
11.3	Chronic Effects (Human Risk Assessment):	Based on the toxicity profile and exposure scenarios for sodium hypochlorite, EPA concludes that the risks from chronic and subchronic exposure to low levels of these pesticides are minimal and without consequence to human health.	
11.4	Tolerance Requirement:	Exempt (EPA document "Index to Pesticide Chemical Names, Part 180 Tolerance Information, and Food and Feed Commodities (by Commodity)" July 2010	

	SECTION 12: ECOLOGICAL INFORMATION			
12.1			Sodium hypochlorite is low in toxicity to avian wildlife, but it is highly toxic to freshwater fish and invertebrates.	
		Freshwater Fish Toxicity:	Atlantic Herring (clupea harengus) $ LC_{50} = 0.033 - 0.097 \text{ mg//l/96 hr, flow through bioassay (pH: 8)} $ Shiner Perch (cymatogaster aggregata) $ LC_{50} = 0.045 - 0.098 \text{ mg/l/96 hr, flow through bioassay (pH: 8)} $ Three Spine Stickleback (gasterosteus aculeatus) $ LC_{50} = 0.141 - 0.193 \text{ mg/l/96 hr, flow through bioassay (pH: 8)} $ Pink Salmon (oncorhynchus gorbuscha) $ LC_{50} = 0.023 - 0.052 \text{ mg/l/96 hr, flow through bioassay (pH: 8)} $ Coho Salmon (oncorhynchus kisutch) $ LC_{50} = 0.026 - 0.038 \text{ mg/l/96 hr, flow through bioassay (pH: 8)} $ English Sole (parophrys vetulus) $ LC_{50} = 0.044 - 0.144 \text{ mg/l/96 hr, flow through bioassay (pH: 8)} $ Fat Head Minnow (pimephales promelas) $ LC_{50} = 0.22 - 0.62 \text{ mg/l/96 hr, flow through bioassay (pH: 7)} $	
	12.1.2	Invertebrate Toxicity:	Water Flea (ceriodaphnia sp. 0) $LC_{50} = 0.006$ mg/l/24 hr Water Flea (daphnia magna) $LC_{50} = 0.07 - 0.7$ mg/l/24 hr Water Flea (daphnia magna) $LC_{50} = 2.1$ mg/l/96 hr Fresh Water Shrimp (gammarus fasciatus) $LC_{50} = 0.4$ mg/l/96 hr No common name (nitocra spinipes) $LC_{50} = 0.40$ mg/l/96 hr Grass Shrimp (palaemonetes pugio) $LC_{50} = 0.52$ mg/l/96 hr	
12.2	Persis	tence:	No data available.	
12.3	Enviro	onmental Fate:	In fresh water, sodium hypochlorite breaks down rapidly into non-toxic compounds when exposed to sunlight. In seawater, chlorine levels decline rapidly; however, hypobromite (which is acutely toxic to aquatic organisms) is formed. EPA believes that the risk of acute exposure to aquatic organisms is sufficiently mitigated by precautionary labeling and National Pollutant Discharge Elimination System (NPDES) permit requirements.	
12.4	Bioco	ncentration:	This material is not expected to bioconcentrate in organisms.	
12.5	Biode	gradation:	This material is inorganic and not subject to biodegradation.	

Revision Date: 07/01/2015 (Supersedes previous revisions)

SECTION 13: DISPOSAL CONSIDERATIONS

Do not contaminate food or feed by storage, disposal, or cleaning of equipment. Product or rinsates that cannot be used should be diluted with water before disposal in a sanitary sewer. This product can be neutralized with sodium bisulfite, sodium thiosulfate, sodium sulfite. Do not confuse these products with sulfates or bisulfates. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination system (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not contaminate water containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA. Dispose of in accordance with all applicable local, County, State, and Federal regulations.

SECTION 14: TRANSPORT INFORMATION 14.1 Inside containers 1.3 gallons or less.						
14.1	Inside containers 1.3 gallons or less.					
	14.1.1 DOT Classification: Consumer Commodity.					
	14.1.2	DOT Hazard Class:	ORM-D.			
	14.1.3	Marking:	Consumer Commodity, ORM-D.			
	14.1.4	Marine Pollutant:	Not listed in Appendix B of the Hazardous Material Table.			
	14.1.5	Deposit Container Returns:	RESIDUE: LAST CONTAINED CONSUMER COMMODITY ORM-D.			
14.2	Inside containers or single containers exceeding 1.3 gallons.					
	14.2.1	DOT Classification: Hypochlorite Solutions.				
	14.2.2	DOT Hazard Class:	8, UN1791, P.G. III.			
	14.2.3	Label:	Corrosive 8.			
	14.2.4	Deposit Container Returns:	RESIDUE: LAST CONTAINED, UN 1791, HYPOCHLORITE SOLUTIONS, 8, PGIII,			
14.3	Reportable Quantity (RQ):		100 lb (45.4 kg) or 80 gallons (based on 12.5% active ingredient)			
14.4						

The regulations that apply to MOTs are found in 49 CFR § 173.6.

This information is not intended to convey all specific regulatory or operational requirements / information relating to this product. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

		SECTION 15: REG	ULATOR	RY INFOR	MATION				
15.1	U.S. F	U.S. Regulations:							
	15.1.1	OSHA HAZCOM (Hazard Communication)	This material is considered hazardous under the HAZCOM Standard (29 CFR 1910.1200)						
		OSHA PSM (Process Safety Management)	Not regula	Not regulated under PSM Standard (29 CFR 1910.119)					
		EPA FIFRA (Federal Insecticide, Fungicide and Rodenticide Act)	EPA Reg. No. :10897-22 (Registered pesticide under 40 CFR 152.10)						
		EPA TSCA (Toxic Substance Control Act)	All components are listed or exempted. TSCA 12(b): This product is not subject to export notification.						
	15.1.5	EPA CERCLA (Comprehensive Environmental Response, Compensation, and Liability Act)	Reportabl (based or	Reportable Quantity (RQ): 45.4 kg (100 lbs) or 80 gallons (based on 12.5% active ingredient).					
		EPA RMP (Risk Management Plan)	Not listed.	Not listed. (40 CFR 68.130)					
15.2									
	15.2.2 15.2.3	Safe Drinking Water and Toxic Enforcement Act of 1986 [Proposition 65, California only]: Small quantities – less than 100 ppm (parts per million) – of impurities, including bromates, may be found in all chlorinating products, including this product. Bromates are derived from bromides, which are present in sodium chloride (table salt) from which chlorine is manufactured. Additional small quantities of bromates may be generated during the disinfection process. Bromates are known by the State of California to cause cancer when administered by the oral (drinking or ingesting) route. Read and follow label directions and use care when handling or using this product. The US Environmental Protection Agency has established a maximum contaminant level (MCL) for bromates in drinking water at 10 ppb (parts per billion). Application of this product in accordance with label directions at use dilution will not exceed this level. This warning is provided pursuant to Proposition 65, Chapter 6.6 of the California Health and Safety Code, which requires the Governor of California to publish a list of chemicals "known to the State to cause cancer or reproductive toxicity." This list is compiled in accordance with the procedures established under the proposition, and can be obtained on the internet from California's Office of Environmental Health Hazard Assessment at http://www.oehha.ca.gov. CDPR (California Department of Pesticide Regulation) Registration No: 10897-22-AA CalARP (California Accidental Release Prevention							
15.3	Canac	Program) anada Regulations:							
	15.3.1	WHMIS (Workplace Hazardous Materials Information System)	orkplace Hazardous • Classification: E (Corrosive Materials)		ria Met by this Chemical: kkin corrosive substance				
	15.3.2	DSL (Domestic Substances List)	All compo	nents of this product are on the DSL.					
15.4	Intern	International Inventory:							
	15.4.1	AICS (Australian Inventory of Cher Substances)	nical	On inventory or in compliance with inventory.					
	15.4.2			On inventory or in compliance with inventory.					
		PICCS (Philippine Inventory of Che and Chemical Substances)		On inventory or in compliance with inventory.					
	15.4.4	IECSC (Inventory of Existing Chem Substances in China)	nical	On inventory or in compliance with inventory.					
	15.4.5	NZIoC (New Zealand Inventory of Chemicals)		On inventory or in compliance with inventory.					

		SECTION 16: OTHE	R INFORMATION	1			
16.1	HMIS III (Hazardous Materials Identification System):						
	16.1.1	HEALTH	2				
	16.1.2	FLAMMABILITY	0				
	16.1.3	PHYSICAL HAZARD	1				
	16.1.4	PERSONAL PROTECTION	See Section 8.				
16.2	NFPA 704 (National Fire Protection Association):						
	16.2.1	HEALTH	2				
	16.2.2 FLAMMABILITY		0				
	16.2.3	INSTABILITY	0				
	16.2.4	SPECIAL	None				
16.3	International Fire Code / International Building Code:		Irritant.				
16.4	ANSI (American National Standards Institute):						
	16.4.1 Hazardous Industrial Chemicals - SDS-Preparation:		Complies with ANSI Z400.1 – 2004.				
	16.4.2 Hazardous Industrial Chemicals - Precautionary Labeling:		Complies with ANSI Z129.1 – 2006.				

Note: The information contained herein, while not guaranteed, was prepared by competent technical personnel and is true and accurate to the best of our knowledge and belief. NO WARRANTY OR GUARANTEE, express or implied, is made regarding the product performance, product stability, or as to any other condition of use, handling, transportation, and storage. Customer use, handling, transportation, and storage may involve additional safety and/or performance considerations. Our technical personnel will be happy to respond to questions regarding safe handling, storage, transportation, and use procedures. The safe handling, storage, transportation, and use procedures remain the sole responsibility of the customer. No suggestions for handling, storage, transportation, or use are intended as or to be construed as recommendations which may infringe on any existing patents or violate any Federal, State, and/or local law and/or regulation, ordinance, standard, etc. This Safety Data Sheet has been prepared by HASA, Inc. staff from test reports and other information available in the public domain.